



ADDITIONAL INFORMATION :

Operating temperature

From -40°C to 80°C

Colors :

Yellow, red, orange, green, black, brown or transparent

Tensile strength

Depending on the model 6 to 8 Kg

Marking :

On request

Type of marking

Hot melt - black color - permanent - unalterable

Packaging :

According to dimensions

Field of application :

Transport, Postal service, Packaging, Bank

Norm :

UL94-V2

Use :

Manual clamping, removal with tool

Material :

Polyamide 6.6 - halogen-free

Typology :

With progressive tightening - not resettable

Rod length :

In black/Natural	Colors
2,5 mm	
2,5 x 75 mm	2,5 x 102 mm
2,5 x 102 mm	2,5 x 197 mm
2,5 x 135 mm	
2,5 x 160 mm	
2,5 x 200 mm	
3,6 mm	
3,6 x 145 mm	3,5 x 140 mm
3,6 x 200 mm	3,5 x 200 mm
3,6 x 290 mm	3,5 x 290 mm
3,6 x 370 mm	
4,8 mm	
4,8 x 120 mm	4,8 x 195 mm
4,8 x 160 mm	4,8 x 291 mm
4,8 x 178 mm	4,8 x 363 mm
4,8 x 195 mm	
4,8 x 250 mm	
4,8 x 300 mm	
4,8 x 360 mm	
4,8 x 390 mm	
4,8 x 430 mm	
7,8 mm	
7,8 x 120 mm	7,8 mm x 375 mm
7,8 x 180 mm	
7,8 x 200 mm	
7,8 x 240 mm	
7,8 x 300 mm	
7,8 x 360 mm	
7,8 x 460 mm	
7,8 x 540 mm	
7,8 x 615 mm	
7,8 x 750 mm	